

8-CH 4-in-1 H.265 DVR



H.265

Features:

Local

- ✓ **8-CH IP-CAM and Analog-8MP (Compatible with AHD/TVI/CVI camera) H.265 Hybrid DVR** with hexaplex operation - simultaneous record, live, playback, backup, control, & remote access
- ✓ **H.265/H.264** video compression/decompression with configurable quality
- ✓ **Max record capabilities: IP-CAM: 240/200fps@1080p/720p, Analog: 40fps@8MP-lite, 96fps@5MP-lite, 120fps@4MP-lite, 160fps@3MP-lite, 120fps@1080p, 240fps@1080p-lite/720p/960H**
- ✓ **Max. 80Mbps incoming bandwidth for IP-CAM**
- ✓ **Smart search & playback**
- ✓ **HDMI * 1, VGA * 1, Main monitor * 1**
- ✓ **Audio in * 4 / audio out * 1**
- ✓ **eSATA connector for HDD extension**
- ✓ **1 or 2 internal SATA HDDs (> 6TB/HDD)**
- ✓ **Alarm in * 8 / alarm out * 1**
- ✓ **Ethernet and USB 3G/4G dongle support for remote access through I.E. or remote app, e-mail alarm notification, FTP file storage, remote setup and software upgrade**

Remote

- ✓ **DVR browser utility**
- ✓ **Free DDNS Server**
- ✓ **Push alarm notification for portable device**
- ✓ **Two-way audio capabilities**
- ✓ **Audio broadcasting**
- ✓ **Dynamic electronics maps for CMS**
- ✓ **Remote setup, monitoring, backup, alarm notification, & remote software upgrade**
- ✓ **Remote access through mobile phone/PDA/Mac/Tablet PC with free iPhone/iPad/Android software app**
- ✓ **1 I.E./Firefox/Chrome/App for multiple DVRs**
- ✓ **Configurable HTTP/SNMP/FTP/Control/Data port**
- ✓ **Support UPnP, P2P, RTSP and QR code**
- ✓ **MS-Windows/iOS/Android SDK for the integration with different applications**

Specification:

Model		DA-1802TA	DA-1800TA
System	O.S.	Embedded Linux 3.0	
	Multiplex	Hexaplex operation - simultaneous record, live, playback, backup, control, & remote access	
Video	Format	IP-CAM: ONVIF Profile S; Analog: NTSC/EIA or PAL/CCIR or AHD/TVI/CVI	
	Input	IP-CAM: up to 8-CH 1080p/720p; Analog: up to 8-CH AHD/TVI/CVI 8MP, BNC, 1Vp-p /75ohm,	
	Main monitor	HDMI, with resolution up to 3840x2160; VGA, with resolution up to 1920x1080; BNC*1, 1Vp-p/75ohm	
	Motion detection	Yes, with configurable detection area & sensitivity	
	Privacy mask	Yes	
Audio	Input	4 RCA-jack connectors, line-in level (100mV-1Vrms)	
	Output	HDMI; 1 RCA-jack connector, line-out level (<1Vrms)	
Record	Compression	Video: H.265/H.264; Audio: ADPCM	
	Max frame rate	IP-CAM: 240/200fps@1080p/720p, Analog: 40fps@8MP-lite, 96fps@5MP-lite, 120fps@4MP-lite, 160fps@3MP-lite, 120fps@1080p, 240fps@1080p-lite/720p/960H Up to 80Mbps incoming bandwidth for IP-CAM	
	Mode	Manual/Schedule/Alarm/Motion	
	Pre-record time	0 - 10 seconds	
	Post-record time	0 - 60 minutes	
Display	Resolution	HDMI - up to 3840*2160, VGA - 1920*1080 ; CVBS	
	Split windows	1/4/7/9	
	Frame rate	Up to 30/25 FPS per display window	
	Digital Zoom	X2, X4	
Playback	Max frame rate	40fps@8MP-lite, 96fps@5MP-lite, 120fps@4MP-lite, 160fps@3MP-lite, 120fps@1080p, 240fps@1080p-lite/720p/960H Max. 4CH 8MP-lite playback in 3840*2160 screen	
	Search	Smart search, Date/time, Camera, Alarm, Motion & Video loss	
	Operation	Play, Fast Forward, Backward, Pause, Stop, Snapshot, etc.	
Storage	HDD	2 x 3.5" SATA HDDs with storage > 6TB/HDD Failure detection & privacy law supported	1 x 3.5" SATA HDD with storage > 6TB/HDD Failure detection & privacy law supported
	HDD Extension	1 optional eSATA connector for up to 5 external HDDs	
	Backup	USB 2.0 x 2; Self playback for backup files	
Alarm	Input	8 contact or TTL/CMOS signals, polarity selectable	
	Output	1 Normally Open or Normally Closed relay outputs	
Network	Ethernet	1 RJ-45 10M/100M/1G bps Ethernet connector	
	USB 3G/4G dongle	Yes	
	Protocol	TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP, TSP, NTP, RTSP, UPnP, P2P	
Remote	Support Windows 10/8/7, N-streaming live view, 1 I.E./Firefox/Chrome/App for unlimited number of DVRs, App for Mac/iPhone/iPad/Android phone and Tablet PC		
Control / POS / GPS	Remote Controller	1 remote controller to control up to 4 DVRs; Optional extension cable	
	RS-232	1 D-type male connector for PTZ, keyboard, POS, or GPS	
	RS-485	2-pin for keyboard and/or PTZ control	
Reliability	System recovery	Auto power on after power loss recovery	
	Watch Dog Timer	Yes	
	Timer	Built-in real time clock	
	Security	Multi-level password (4 levels, up to 18 accounts) protection with authentication key for remote access	
Weights & Measures	Dimension	435(W) x 285(D) x 55(H)mm	320(W) x 210(D) x 50(H)mm
	Weight	3.0 KG (without HDD)	2.2 KG (without HDD)
Power	Source	+12VDC	
	Consumption	60W Max.	36W
Operating Temperature	0°C ~ +55°C		