


DK-1114 5MP 4CH DVR (IPC Hybrid)



Specification:

Model		DK-1114
System	Multiplex	Hexaplex operation - simultaneous record, live, playback, backup, control, & remote access
Video	Format	IP-CAM: ONVIF Profile S / T ; Analog: NTSC/EIA or PAL/CCIR or AHD/TVI/CVI
	Input	IP-CAM: up to 2-CH 1080p/720p, IP-CAM supports up to 5MP Analog: up to 4-CH AHD/TVI/CVI 5MP, BNC, 1Vp-p /75ohm Total Max. 6CH: 4CH Analog + 2CH IP-CAM
	Output	HDMI/VGA - up to 1920*1080 ; CVBS
Audio	Input	4 RCA-jack connectors, line-in level (100mV-1Vrms) ; 4-CH via Coaxial cable
	Output	HDMI; 1 RCA-jack connector, line-out level (up to 1Vrms)
Record	Compression	Audio: ADPCM
	Max frame rate	IP-CAM: 5MP/1080p/720p, Up to 40Mbps incoming bandwidth for IP-CAM Analog: 24fps@5MP, 48fps@5MP-lite, 60fps@4MP-lite, 80fps@3MP-lite, 60fps@1080p, 120fps@1080p-lite/720p/960H
	Pre-record time	0 - 10 seconds
	Post-record time	0 - 60 minutes
Display	Split windows	1/4/7
	Frame rate	Up to 30/25 FPS per display window
	Digital Zoom	X2, X4
Playback	Max frame rate	24fps@5MP, 48fps@5MP-lite, 60fps@4MP-lite, 80fps@3MP-lite, 60fps@1080p, 120fps@1080p-lite/720p/960H
	Search	Smart search, Date/time search, POS search, Camera, Alarm, Motion & Video loss
	Operation	Play, Fast Forward, Backward, Pause, Stop, Snapshot, etc.
Storage	HDD	1 x 3.5" SATA HDD (Up to 10TB capacity for each HDD)
	HDD Extension	Optional 1 eSATA connector
	Backup	USB 2.0 x 2 ; Self playback for backup files
Alarm	Input	4 contact (Low Active)
	Output	1 Normally Open or Normally Closed relay outputs
Network	Ethernet	1 RJ-45 10M/100M bps Ethernet connector
	Protocol	TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP, TSP, NTP, RTSP, UPnP, P2P
	Remote Users	Up to 8 users simultaneously
	Remote	Support Windows 10/8/7, N-streaming live view, I.E/Firefox/Chrome DVRs, App for Mac/iPhone/iPad/Android phone and Tablet PC
Control / POS / GPS	RS-485	2-pin for keyboard and/or PTZ control
	RS-232	Optional 1 D-type male connector
Artificial Intelligence		Support for people and car detection (Optional, 1 USB AI stem for 2 channels detection)
Reliability	System recovery	Auto power on after power loss recovery (with Watch Dog Timer)
	Timer	Built-in real time clock
Weights & Measures	Security	Multi-level password (4 levels, up to 18 accounts) protection with authentication key for remote access
	Dimension / Weight	255(W) x 220(D) x 42(H)mm / 0.8 KG (without HDD)
Power	Source / Consumption	+12VDC, 2.5A / 30W Max.
		Install 1 HDD than or equal to 3TB, requires the purchase of a higher amperage adapter. (Optional 5A or above)
Operating Temperature		-5°C ~ +60°C