


DK-1236 8MP 16CH DVR (IPC Hybrid)



Specification:

Model		DK-1236
System	Multiplex	Hexaplex operation - simultaneous record, live, playback, backup, control, & remote access
Video	Format	IP-CAM: ONVIF Profile S / T ; Analog: NTSC/EIA or PAL/CCIR or AHD/TVI/CVI
	Input	IP-CAM: up to 16-CH 1080p/720p, IP-CAM supports up to 8MP Analog: up to 16-CH AHD/TVI/CVI 8MP, BNC, 1Vp-p /75ohm, Total Max: 16-CH Analog or IP-CAM
	Output	HDMI with resolution up to 3840x2160; VGA, with resolution up to 2560x1600; CBVS
Audio	Input	4 RCA-jack connectors, line-in level (100mV-1Vrms) ; 16-CH via Coaxial cable
	Output	HDMI; 1 RCA-jack connector, line-out level (up to 1Vrms)
Record	Compression	Audio: ADPCM
	Max frame rate	IP-CAM: 240fps@1080p, 480/400fps@720p, Up to 80Mbps incoming bandwidth for IPCAM Analog: 80fps@8MP-lite, 192fps@5MP-lite, 240fps@4MP-lite, 320fps@3MP-lite, 240fps@1080p, 480fps@1080p-lite/720p/960H
	Pre-record time	0 - 10 seconds
	Post-record time	0 - 60 minutes
Display	Split windows	1/4/7/9/10/13/16
	Frame rate	Up to 30/25 FPS per display window
	Digital Zoom	X2, X4
Playback	Max frame rate	80fps@8MP-lite, 192fps@5MP-lite, 240fps@4MP-lite, 320fps@3MP-lite, 240fps@1080p, 480fps@1080p-lite/720p/960H
	Search	Smart search, Date/time search, POS search, Camera, Alarm, Motion & Video loss
	Operation	Play, Fast Forward, Backward, Pause, Stop, Snapshot, etc.
Storage	HDD & Extension	2 x 3.5" SATA HDD (or Optional 1 x 3.5" SATA HDD + 1 eSATA connector for up to 5 external HDDs)
	Backup	USB 2.0 x 2 ; Self playback for backup files
Alarm	Input	8 contact or TTL/CMOS signals, polarity selectable
	Output	1 Normally Open or Normally Closed relay outputs
Network	Ethernet	1 RJ-45 10M/100M/1000M bps Ethernet connector
	Protocol	TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP, TSP, NTP, RTSP, UPnP, P2P
	Remote Users	Up to 8 users simultaneously
	Remote	Support Windows 10/8/7, N-streaming live view, I.E/Firefox/Chrome DVR, App for Mac/iPhone/iPad/Android phone and Tablet PC
Control / POS / GPS	RS-485	2-pin for keyboard and/or PTZ control
	RS-232	Optional 1 D-type male connector
Reliability	System recovery	Auto power on after power loss recovery (with Watch Dog Timer)
	Timer	Built-in real time clock
	Security	Multi-level password (4 levels, up to 18 accounts) protection with authentication key for remote access
Weights & Measures	Dimension / Weight	320(W) x 250(D) x 60(H)mm / 2.0 KG (without HDD)
Power	Source / Consumption	+12VDC, 5A / 60W Max.
Operating Temperature		-5°C ~ +60°C