

2MP Network Bullet Camera Vari-Focal 40M IR



IB24F1-V2

Specification

Image Sensor	SONY 1/2.8" 2MP Starvis CMOS
Compression	Video: H.265/H.264; Audio: G711、G726
Onvif	Profile S / Profile T
Video Streaming	Dual Streams
Video Resolution & Frame Rate	Main Stream: 1920x1080@30(25)fps, 1280x720@30(25)fps, 960x540@30(25)fps, 720x480@30(25)fps, 360x240@30(25)fps Sub Stream: 720x480@30(25)fps, 640x360@30(25)fps, 360x240@30(25)fps, 320x180@30(25)fps
Video Bit Rate	64Kbps-8Mbps, Support CBR-VBR
Wide Dynamic Range	Yes
Digital Zoom	Yes
White balance	Auto / Indoor / Outdoor / Manual
Day/Night	Day mode / Night mode / External control
Shutter / Exposure Model	Auto / 1/30(25) ~ 1/10000
Digital Noise Reduction	2DNR、3DNR
Hight Light Control	Yes
Smart Defog	Yes
Signal to Noise Ratio	≥ 50db(AGC Off)
OSD Display	Camera name/ Date and Time, Display position can be adjusted
Image Settings	Brightness, Saturation, Contrast, Hue, Sharpness, Image Enhancement, Anti-flicker Flip Mode Adjustable by Client Software or Web Browser
Lens	2.8~ 12mm 3MP lens
Min. illumination	0.001 Lux @F1.2 0 Lux @F1.2 (IR On)
Day & Night	ICR
IR Range	4pcs Array Led ; 40M IR distance
ROI (Region of Interest)	4 Zones
Privacy Mask	8 Zones
Audio IN	1 RCA-jack connector
Alarm I/O	optional
Network Interface	10M / 100M Base-TX Ethernet
Protocol	IPv4/HTTP/FTP/SMTP/DNS/DDNS/RTSP/TCP/UDP/DHCP/RTP/NTP/ARP/P2P
Max. Connections	4
Browser	IE
Remote	Support Windows 10/8/7, App for Mac/iPhone/iPad/Android phone and Tablet PC
Waterproof	IP66
Working Environment	-20°C ~ 60°C, 0 ~ 90% RHG
Dimension / Weight	100(W) x 80(H) x 240(L) mm / 650g.
Power Consumption	12 VDC, max. 7.2 W Optional: POE cable - DC12V 1.3A 15W