

5MP Network Dome Camera Vari-Focal 30M IR

ID53H5-V2



Specification

Image Sensor	SC530AI SmartClarity® -2 Series 1/2.7" 5MP CMOS
Compression	Audio: G711
Onvif	Profile S / Profile T
Video Streaming	Dual Streams
Video Resolution & Frame Rate	Main Stream: 2880x1620@30(25)fps, 2560x1440@30(25)fps, 2048x1536@30(25)fps, 1920x1080@30(25)fps, 1280x720@30(25)fps, 960x540@30(25)fps, 720x480@30(25)fps, 640x360@30(25)fps Sub Stream: 1280x720@30(25)fps, 960x540@30(25)fps, 720x480@30(25)fps, 640x360@30(25)fps, 360x240@30(25)fps, 320x180@30(25)fps
Video Bit Rate	64Kbps-12Mbps, Support CBR-VBR
Wide Dynamic Range	Yes
Digital Zoom	Yes
White balance	Auto / Indoor / Outdoor / Manual
Day/Night	Auto / Day mode / Night mode / External control
Shutter / Exposure Model	Auto / 1/30(25) ~ 1/10000
Digital Noise Reduction	2DNR、3DNR
High Light Control	No
Smart Defog	No
Signal to Noise Ratio	≥ 40db(AGC Off)
OSD Display	Camera name/ Date and Time, Display position can be adjusted
Image Settings	Brightness, Saturation, Contrast, Sharpness, Image Enhancement, Anti-flicker Flip Mode Adjustable by Client Software or Web Browser
Lens	F1.4 2.8~ 12mm 5MP lens
Adjustment range	Pan: 0°~ 360° Tilt: 0°~ 90°
Min. illumination	0.01 Lux @F1.2 0.02 0 Lux @F1.2 (IR On)
Day & Night	ICR
IR Range	4pcs Array Led ; 30M IR distance
ROI (Region of Interest)	4 Zones
Privacy Mask	8 Zones
Audio In / Out	1 RCA-jack connector / 1 RCA-jack connector
Alarm In / Out	1 IN / 1 OUT
On-Board Storage	Built-in memory card slot, support micro SD / micro SDHC / micro SDXC card, up to 256 GB
Intelligent Detection Function	Motion Detection Optional: Video Tampering, Line Crossing Detection, Intrusion Detection, Loitering Detection
Network Interface	10M / 100M Base-TX Ethernet
Protocol	IPv4/HTTP/SMTP/DNS/DDNS/RTSP/TCP/UDP/DHCP/RTP/NTP/ARP/P2P
Max. Connections	4
Browser	IE (support Edge/Firefox/Chrome in March for Phase 1.)
Remote	Support Windows 11/10/8/7, App for Mac/iPhone/iPad/Android phone and Tablet PC
Vandal-Resistant	IK10
Waterproof	IP68
Working Environment	-20°C ~ 60°C, 0 ~ 90% RHG
Dimension / Weight	120(H) x 140 (Ø) mm / 800g.
Power Consumption	12 VDC, max. 7 W POE (IEEE802.3af)